

Attenuators

N-Male To N-Female Connector

Part No.	Frequency Range (GHz)	Power (W)	Attenuation (dB)	VSWR	Z (Ω)	Dimensions (mm)	Weight (grams)
CSG 7300AT-5-NN	DC - 3.0	5	3 ~ 6/10/20/30/40/50/60	$\leq 1.15 : 1$	50	71.5 x 18	70
CSG 7300AT-20-NN	DC - 3.0	20	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	104.5 x 47	235
CSG 7300AT-25-NN	DC - 3.0	25	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	126.5 x 53.5	355
CSG 7300AT-30-NN	DC - 3.0	30	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	126.5 x 53.5	355
CSG 7300AT-40-NN	DC - 3.0	40	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	132.5 x 60	425
CSG 7300AT-50-NN	DC - 3.0	50	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	132.5 x 60	425
CSG 7300AT-75-NN	DC - 3.0	75	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	165 x 80	985
CSG 7300AT-100-NN	DC - 3.0	100	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	165 x 80	985
CSG 7300AT-150-NN	DC - 3.0	150	50	$\leq 1.25 : 1$	50	230 x 160 x 90	3400

