



VHF RECEIVER MULTICOUPLER CSG 3138225-4RXMC

PARAMETER	SPECIFICATIONS
Frequency Band	138 – 225 MHz
Number of Channels	4
Pass Band	3 MHz
Numbers of Resonators	5
Rx / Rx Isolation	≥ 20 dB
Amplifier Gain	≥ 30 dB
VSWR @ Resonance (Max.)	1.25 :1
Impedance	50 Ω
Connectors Input / Output	N / N
Amplifier type	Bipolar
Amplifier Noise figure	3.0 dB
Amplifier 3rd Order IP	≥ 42 dBm
Amplifier 1 dB Comp	≥ 21 dBm
System NF (typ.)	5 dB
Amplifier Bias Voltage	13.6 VDC
Amplifier Current Drawn	200 mA
System Voltage	230 / 115 VAC
Temperature Range	-30 to +60 °C
Dimensions Approx.(H x W x D)	134 x 483 x 254 mm
Weight Approx.	5.5 Kg

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT

CSG Networks Pvt Ltd. 109-110, HUDA Industrial Area Sector-59 Faridabad, Haryana-121004 INDIA

E-mail : sales@csgnets.com, Website : www.csgnets.com