

2.4 GHz Magnetic Mount Antenna CSG 62405 MMN

PARAMETERS	SPECIFICATIONS
Frequency Range	2400 ~ 2500 MHz
Gain	5.5 dBi
VSWR	$\leq 1.5 : 1$
Horizontal Beamwidth	360°
Vertical Beamwidth	360°
Polarization	Vertical
Max. Power	50 Watt
Impedance	50 Ω
Connector	RP-SMA / TNC(M) or MMCX(M) or MC Card
Height (Approx.)	300 mm
Weight (Approx.)	0.15 kg
Colour	Silver
Working Temperature	-40 °C ~ +60 °C



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT

2.4 GHz Magnetic Mount Antenna CSG 62408 MMN

PARAMETERS	SPECIFICATIONS
Frequency Range	2400 ~ 2500 MHz
Gain	8.0 dBi
VSWR	$\leq 1.5 : 1$
Horizontal Beamwidth	360°
Vertical Beamwidth	360°
Polarization	Vertical
Max. Power	50 Watt
Impedance	50 Ω
Connector	RP-SMA / TNC(M) or MMCX(M) or MC Card
Height (Approx.)	500 mm
Weight (Approx.)	0.1 kg
Colour	Silver
Working Temperature	-40 °C ~ +60 °C



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT