

3.5 GHz Omni Directional Antenna

CSG 63507 ODN

PARAMETERS	SPECIFICATIONS
Frequency Range	3400~3700 MHz
Gain	7.0 dBi
VSWR	$\leq 1.5:1$
E Plane Beamwidth (3 dB)	20°
Polarization	Vertical
Max. Power	100 Watts
Impedance	50 Ω
Connector	N (F)
Element Housing Material	Fiberglass
Height (Approx.)	500 mm
Weight (Approx.)	0.25 Kg
Electrical Down Tilt	0°
Max. Wind Velocity	210 km/hr
Mounting Hardware	$\Phi 35$ - $\Phi 50$ mm
Lightning Protection	DC Ground



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT

3.5 GHz Omni Directional Antenna

CSG 63509 ODN

PARAMETERS	SPECIFICATIONS
Frequency Range	3400~3700 MHz
Gain	9.0 dBi
VSWR	$\leq 1.5:1$
E Plane Beamwidth (3 dB)	12°
Max. Power	100 Watts
Polarization	Vertical
Impedance	50
Connector	N (F)
Element Housing Material	Fiberglass
Height (Approx.)	800 mm
Weight (Approx.)	0.40 Kg
Electrical Down Tilt	0°
Max. Wind Velocity	210 km/hr
Mounting Hardware	Φ35-Φ50 mm
Lightning Protection	DC Ground



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT

3.5 GHz Omni Directional Antenna

CSG 63511 ODN

PARAMETERS	SPECIFICATIONS
Frequency Range	3400~3700 MHz
Gain	11.0 dBi
VSWR	$\leq 1.5:1$
E Plane Beamwidth (3 dB)	90°
Max. Power	150 Watts
Polarization	Vertical
Impedance	50 Ω
Connector	N (F)
Element Housing Material	Fiberglass
Height (Approx.)	1.0 meters
Weight (Approx.)	0.70 Kg
Electrical Down Tilt	0°
Max. Wind Velocity	210 km/hr
Mounting Hardware	$\Phi 35$ - $\Phi 50$ mm
Lightning Protection	DC Ground



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT