

3.5 GHz Panel Antenna

CSG 63516 PN

PARAMETERS	SPECIFICATIONS
Frequency Range	3400~3700 MHz
Gain	16.0 dBi
VSWR	$\leq 1.5:1$
H Plane Half power Beamwidth	30°
E-Plane Half Power Beamwidth	24°
Front to Back Ratio	≥ 30 dB
Polarization	Vertical
Max. Power	100 Watts
Impedance	50 Ω
Connector	N (F)
Element Material	Brass
Radome Material	UV-resistance ABS
Dimensions (H x W x D)	250 x 190 x 50 mm
Weight (Approx.)	1.5 Kg
Lightning Protection	DC Ground



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT

3.5 GHz Panel Antenna

CSG 63520 PN

PARAMETERS	SPECIFICATIONS
Frequency Range	3400~3700 MHz
Gain	20.0 dBi
VSWR	$\leq 1.5:1$
H Plane Half power Beamwidth	14°
E-Plane Half Power Beamwidth	15°
Front to Back Ratio	≥ 25 dB
Polarization	Vertical or Horizontal
Max. Power	100 Watts
Impedance	50 Ω
Connector	N (F)
Element Material	Brass
Radome Material	UV-resistance ABS
Dimensions (H x W x D)	340 x 340 x 45 mm
Weight (Approx.)	3.0 Kg
Lightning Protection	DC Ground



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT