

5.0 GHz Solid Dish Antenna

CSG 651032 SDN

PARAMETERS	SPECIFICATIONS
Frequency Range	5150 ~ 5350 MHz
Gain	32.5 dBi
VSWR	$\leq 1.5 : 1$
Horizontal Beamwidth	5°
Vertical Beamwidth	5°
Front to Back Ratio	≥ 38 dB
Polarization	Vertical / Horizontal
Max. Power	100 Watt
Impedance	50 Ω
Connector	N(F)
Diameter (Approx.)	900 mm
Weight (Approx. Including Clamp)	10.0 kg



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT

5.8 GHz Solid Dish Antenna

CSG 658032 SDN

PARAMETERS	SPECIFICATIONS
Frequency Range	5725 ~ 5850 MHz
Gain	32.5 dBi
VSWR	$\leq 1.5 : 1$
Horizontal Beamwidth	6°
Vertical Beamwidth	6°
Front to Back Ratio	≥ 38 dB
Polarization	Vertical / Horizontal
Max. Power	100 Watt
Impedance	50 Ω
Connector	N(F)
Diameter (Approx.)	900 mm
Weight (Approx. Including Clamp)	10.0 kg



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT