

5.8 GHz Omni Directional Antenna CSG 65808 ODN

PARAMETERS	SPECIFICATIONS
Frequency Range	5725 ~ 5850 MHz
Gain	8.0 dBi
VSWR	$\leq 1.5 : 1$
Half Power Beamwidth	16°
Electrical Down Tilt	0°
Polarization	Vertical
Max. Power	100 Watt
Impedance	50 Ω
Connector	N(F)
Element Housing Material	Fiberglass
Diameter (Approx.)	Φ 20 mm
Height (Approx.)	350 mm
Weight (Approx.)	0.2 kg
Rated Wind Velocity	220 km/hr
Mounting Hardware	Φ 35 ~ Φ 50 mm



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT

5.8 GHz Omni Directional Antenna CSG 65810 ODN

PARAMETERS	SPECIFICATIONS
Frequency Range	5725 ~ 5850 MHz
Gain	10.0 dBi
VSWR	$\leq 1.5 : 1$
Half Power Beamwidth	10°
Electrical Down Tilt	0°
Polarization	Vertical
Max. Power	100 Watt
Impedance	50 Ω
Connector	N(F)
Element Housing Material	Fiberglass
Diameter (Approx.)	Φ 20 mm
Height (Approx.)	670 mm
Weight (Approx.)	0.325 kg
Rated Wind Velocity	220 km/hr
Mounting Hardware	Φ 35 ~ Φ 50 mm



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT

5.8 GHz Omni Directional Antenna CSG 65812 ODN

PARAMETERS	SPECIFICATIONS
Frequency Range	5725 ~ 5850 MHz
Gain	12.0 dBi
VSWR	$\leq 1.5 : 1$
Half Power Beamwidth	6°
Electrical Down Tilt	0°
Polarization	Vertical
Max. Power	100 Watt
Impedance	50 Ω
Connector	N(F)
Element Housing Material	Fiberglass
Diameter (Approx.)	Φ 21 mm
Height (Approx.)	920 mm
Weight (Approx.)	0.7 kg
Rated Wind Velocity	220 km/hr
Mounting Hardware	Φ 35 ~ Φ 50 mm



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT