

380 – 2700 MHz MIMO Panel Antenna

CSG 6382708X PF_x2

PARAMETERS	SPECIFICATIONS		
Operating Frequency	380-698MHz	698-960MHz	1710-2700MHz
Gain	4.0 dBi	5.0 dBi	8.0 dBi
Azimuth Beam width	80°	140°	40°
Elevation Beam width	80°	95°	50°
VSWR	≤2.5 : 1	≤2.5	≤2.0 : 1
Front to Back ratio	25 dB		
Polarization	Vertical		
Impedance	50 Ω		
Max Power Input	50 Watts		
Connectors	FME Female		
Water Proofing	IP54		
Flammability	UL94HB		
Rated Wind Load	60 m/s		
Operating Temperature	-40°C to +70°C		
Application	Outdoor		
Back Plate	Oxidation processed Aluminium		
Radome Material	PVC		
Radome Color	Grey		
Cable Type	LMR 200 with Black Jacket		
Cable Length	8 Meter		
Dimensions (H X W X D)	627 mm x 284 mm x 91 mm		
Mounting Style	Pole Mount		



Note: Mounting Hardware and Brackets are supplied with Antenna

WE ALSO UNDERTAKE DESIGNS PER YOUR REQUIREMENT

CSG Networks Pvt.Ltd. 109-110, HUDA Industrial Area Sector-59 Faridabad, Haryana-121004 INDIA

E-mail: sales@csgnets.com , Website: www.csgnets.com