

ATTENUATORS

N-MALE TO N-FEMALE CONNECTOR

Part No.	Frequency Range (GHz)	Power (W)	Attenuation (dB)	VSWR	Z (Ω)	Dimensions (mm)	Weight (Grams)
CSG 7300AT-5-NN	DC - 3.0	5	3 ~ 6/10/20/30/40/50/60	$\leq 1.15 : 1$	50	71.5 x 18	70
CSG 7300AT-20-NN	DC - 3.0	20	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	104.5 x 47	235
CSG 7300AT-25-NN	DC - 3.0	25	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	126.5 x 53.5	355
CSG 7300AT-30-NN	DC - 3.0	30	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	126.5 x 53.5	355
CSG 7300AT-40-NN	DC - 3.0	40	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	132.5 x 60	425
CSG 7300AT-50-NN	DC - 3.0	50	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	132.5 x 60	425
CSG 7300AT-75-NN	DC - 3.0	75	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	165 x 80	985
CSG 7300AT-100-NN	DC - 3.0	100	3 ~ 6/10/20/30/40/50/60	$\leq 1.20 : 1$	50	165 x 80	985
CSG 7300AT-150-NN	DC - 3.0	150	50	$\leq 1.25 : 1$	50	230 x 160 x 90	3400



RF CONNECTORS / ADAPTORS / CABLES & CABLE ASSEMBLIES

RF & LOW LOSS CABLES

50 Ω Cables : RG 58, RG 213, RG214
LMR 200, LMR 400, 1/4", 1/2" & 7/8" dia all types.

CONNECTORS for use with 50 Ω RF Cables

- N(Male) / N (Female) / RP-N
- BNC (Male) / BNC (Female)
- TNC (Male) / TNC (Female) / RP-TNC
- SMA(Male) / SMA(Female) / RP-SMA
- PL 259 / UHF (Male) / UHF (Female)
- MINI PL 259 / UHF (Male) / UHF (Female)
- MMCx/ MC Card / SMB / SSMB / FME

Special Categories for use with Low Loss Cables

- DIN 7/16 for 1/4", 1/2" & 7/8", 1 1/4", 1 5/8" dia. cable
- N for 1/4", 1/2" & 7/8", 1 1/4", 1 5/8" dia. cable

ADAPTORS

- In line DIN 7/16, N, TNC, BNC, UHF, SMA Male / Female



WE UNDERTAKE DESIGNS PER YOUR REQUIREMENT